

SPECIFICATIONS

Product Description: Part Number: Style: STO-SACK 9500-15SB, 9500-25SB, 9550-15SB, 9550-25SB SELF-STORAGE BAG WITH DUCTING

GENERAL DESCRIPTION:

This lightweight self-storage bag with attached ducting is designed for convenient storage and easy transport of ducting. Different diameters and lengths of ducting available.

BAG FEATURES:

- Flame retardant materials
- · Fastening belt on bag to attach directly to blower
- Drawstring closure to store ducting in bag
- Built-in carry handle

DUCTING FEATURES:

- Ideal for moving large volumes of air, smoke or fumes using portable and temporary ventilation blowers under positive pressure
- Vinyl and polyester materials
- Single ply
- PVC-coated
- Temperature range: -20° F to 180° F (-28.8° C to 82.22° C)
- Retractable, non-collapsible design
- Class 1 hard drawn spring steel wire helix
- Meets ASTM 227 specs
- Meets flame retardant requirements of UL94V-0
- Yellow color with black weather-strip
- Fastening cuff to attach bag to blower

AVAILABLE:

Part No.	Ducting Diameter	Ducting Length	End-Straps
9500-15SB	8" (20.3 cm)	15' (4.57 m)	Dual
9500-25SB	8" (20.3 cm)	25' (7.62 m)	Dual
9550-15SB	12" (30.48 cm)	15' (4.57 m)	Dual
9550-25SB	12" (30.48 cm)	25' (7.62 m)	Dual

ACCESSORIES:

Part No.	Diameter	Description	
9500-01	8" (20.3 cm)	8" Duct to Duct Connector with raised lip	
9510-50	8" (20.3 cm)	8" Manhole Ventilation Passthru (MVP)	
9550-01	12" (30.48 cm)	12" Duct to Duct Connector with raised lip	
9510-60	12" (30.48 cm)	12" Manhole Ventilation Passthru (MVP)	



864-846-8740

800-622-3530

FAX: 800-362-7231