

## SPECIFICATIONS

Product Description:       **DUCTING,**  
 Part Number:               **9600-15, 9600-25**  
 Style:                         **16" (40.6 cm) RETRACTABLE**

**GENERAL DESCRIPTION:**

This product is lightweight, retractable, and designed for maximum air handling capabilities. Dual direction flow with minimum friction loss.



**CONSTRUCTION:**

- Vinyl and polyester materials
- Single ply
- PVC-coated
- Temperature range: -20° F to 180° F (-28.8° C to 82.2° C)
- Retractable, non-collapsible design.
- Class 1 hard drawn spring steel wire helix
- Meets ASTM 227 specs
- UL 94V-0 flame-retardant
- Yellow color with black weather-strip
- Fastening cuffs at both ends

**AVAILABLE:**

PN	Diameter	Length	End-Straps
<b>9600-15</b>	16" (40.6 cm)	15' (4.57 m)	Dual
<b>9600-25</b>	16" (40.6 cm)	25' (7.62 m)	Dual

**ACCESSORIES:**

PN	Ducting Size	Description
<b>9600-01</b>	16" (40.6 cm)	Duct to Duct Connector with raised lip
<b>9600-35</b>	16" (40.6 cm)	Storage Rack for 16" (40.6 cm) Ducting, up to 25' (7.62 m) Ducting
<b>9600-45</b>	16" (40.6 cm)	Storage Bag
<b>9600-50</b>	16" 40.6 cm) to 8" (20.3 cm)	Reducer from 16" (40.6 cm) blower to 8" (20.3 cm) ducting