

Model DPH-8 • 32 GPM • 300 PSI

* Shown with optional Wheel and Handle Kit.



- Automatic Pressure Regulator with Inlet Bypass
- Stainless Steel Liquid-Filled Gauge Ensure Accurate Readings, with Less Flutter
- Inlet Hose Assembly, with Stainless Steel Mesh Filter
- Rugged Roll-Cage Construction Protects Pump from Damage

The DPH-8, a triple diaphragm pump, recognized as the most versatile sought after hydrostatic test pump on the market. Exceptionally smooth and quiet operation in comparison to the twin diaphragm, the triple diaphragm requires no pressure accumulator. EXCLUSIVE, to the RICE Hydro triple diaphragm pump is the "DURApHragm technology", where pressure is spread across the entire face of the diaphragm virtually eliminating torn, damaged diaphragms. Another design upgrade is the inlet suction diaphragm assembly, eliminating the concern for ruptured diaphragms caused by pressure feeding, is now a separate assembly from the pump, which can be added at any time. The diaphragm design allows for the handling of up to a 10% chlorine solution, and the ability to be run dry without damaging the pump. A large volume, medium pressure test pump, this unit is recommended for testing up to 96" diameter lines. The DPH-8 is available with Briggs & Stratton, Robin or Honda engine options.

HYDROSTATIC PUMP SPECIFICATIONS

- **INLET:** 1 1/4"
Inlet hose assembly included on units not purchased with tank accessory
- **OUTLET:** 3/4" with Quick Connect Couplings
High pressure 8ft. hose
Pressure regulator adjusting to 300 PSI
- **PUMP:** Triple Diaphragm, inner oil bath protection, innovative "DURApHragm technology", and helical gear reduction.
- **OUTPUT FLOW:** 32 GPM
- **MAX. OUTPUT PRESSURE:** 300 PSI
- **ENGINE:** 270 CC, air-cooled, 4-cycle, Briggs or Honda engine option available

DPH-8	
STEMAR Rental Class No.	5549
STEMAR Sales Item No.	PUMP 125



*DPH-8 Shown with optional wheel and handle kit.



The **DP Series** hydrostatic test pumps are large volume, medium pressure units, with flow rates up to 56 GPM and pressures up to 600 PSI. Designed to quickly fill and test lines up to 96" in diameter. Unique to the diaphragm pumps are their ability to handle up to a 10% chlorine solution, and can be run dry without damage to the pump.

MODELS:

DPH-8	32 GPM	300 PSI
Triple diaphragm,	270 CC engine	
DPH-56/250	56 GPM	250 PSI
Six diaphragm,	389 CC engine	

A C C E S S O R I E S

Pressure Feed Tanks

The pressure feed tank accessory allows the inlet pressure feeding of the diaphragm series test pumps.

Saving time, labor, repair and maintenance costs, by virtually eliminating the rupture/damage of diaphragms caused by excessive inlet pressure. The heavy duty polypropylene tank provides easy access for chemical treatment of water lines and test environment, eliminating the need for a 55 gallon water drum.



Wheel & Handle Kits

Rice Hydro offers a wheel kit accessory, making your hydrostatic test pump truly portable, with increased mobility. Saving time and labor, while minimizing cost and liability.