

STEMAR EQUIPMENT & SUPPLY CO., INC.

Serving Underground Construction Since 1922

T-Handle Gripper

T-Handle Aluminum Gripper® Plug Features:

- Ideal for long term applications
- 6" - 12" plugs are sized for concrete, clay, and SDR 26 and 35 pipe
- 15" and 18" plugs are sized for concrete and clay pipe sizes only
- Available with or without bypass
- Can be used for sewer air pressure tests
- Adaptable to almost any pipe type and ID with optional rubber gaskets



Equipped with:

- Heavy duty aluminum body and T-handle
- Chemical resistant neoprene o-ring

Part Number	Nominal Size	Range of Use	Maximum Back Pressure	Length	Product Weight	Bypass Diameter
-------------	--------------	--------------	-----------------------	--------	----------------	-----------------

Mechanical Plug with Bypass

272949	6" (150 mm)	5.7"-6.3" (144-160 mm)	17 psi (1,2 bar)	40 ft. (12 M)	9.7" (247 mm)	6.5 lbs (3 kg)	1/4" MNP
272957	8" (200 mm)	7.7"-8.3" (196-211 mm)	17 psi (1,2 bar)	40 ft. (12 M)	9.7" (247 mm)	9.5 lbs (4.3 kg)	3/4" MNP
272965	10" (250 mm)	9.8"-10.3" (248-262 mm)	17 psi (1,2 bar)	40 ft. (12 M)	9.7" (247 mm)	12.5 lbs (5.7 kg)	3/4" MNP
272973	12" (300 mm)	11.7"-12.3" (297-312 mm)	13 psi (0,9 bar)	30 ft. (9.1 M)	9.7" (247 mm)	16 lbs (7.3 kg)	3/4" MNP
272981	15" (380 mm)	14.8"-15.3" (377-388 mm)	13 psi (0,9 bar)	30 ft. (9.1 M)	9.7" (247 mm)	24 lbs (10.7 kg)	3/4" MNP
272998	18" (460 mm)	17.7"-18.3" (450-465 mm)	8.7 psi (0,61 bar)	20 ft. (6.1 M)	9.7" (247 mm)	31 lbs (14 kg)	3/4" MNP
PLUGS120DT	20" (507 mm)	19.8"-20.7" (502-525 mm)	5 psi (0,3 bar)	12 ft. (3.7 M)	9.7" (247 mm)	32 lbs (14.5 kg)	1 1/4 " MNP
PLUGS124DT	24" (610 mm)	23.60"-24.75" (599-628mm)	5psi (0.3 bar)	12 ft. (3.7M)	10.25" (260mm)	40 lbs (18.1 kg)	2" MNP

Mechanical Test Plug Plain

272892	6"(150 mm)	5.7"-6.3" (144-160 mm)	17 psi (1,2 bar)	40 ft. (12 M)	9.7" (247 mm)	6 lbs (2.7 kg)	
272906	8" (200 mm)	7.7"-8.3" (196-211 mm)	17 psi (1,2 bar)	40 ft. (12 M)	9.7" (247 mm)	9 lbs (4.1 kg)	
272914	10" (250 mm)	9.8"-10.3" (248-262 mm)	17 psi (1,2 bar)	40 ft. (12 M)	9.7" (247 mm)	12 lbs (5.4 kg)	
272922	12" (300 mm)	11.7"-12.3" (297-312 mm)	13 psi (0,9 bar)	30 ft. (9.1 M)	9.7" (247 mm)	15.5 lbs (7 kg)	
272930	15" (380 mm)	14.8"-15.3" (377-388 mm)	13 psi (0,9 bar)	30 ft. (9.1 M)	9.7" (247 mm)	23 lbs (10.4 kg)	
272888	18" (460 mm)	17.7"-18.3" (450-465 mm)	8.7 psi (0,61 bar)	20 ft. (6.1 M)	9.7" (247 mm)	30 lbs (13.6 kg)	
PLUGS120P	20" (507 mm)	19.8"-20.7" (502-525 mm)	5 psi (0,3 bar)	12 ft. (3.7 M)	9.7" (247 mm)	32 lbs (14.5 kg)	

MNP – Male National Pipe Thread

Always block plugs when conducting air tests.

Note: WIDTH FOR THE 10" & 12" MECHANICAL PLUG IS 3 1/2"

-----MANUFACTURING AND WHOLESALE CONSTRUCTION EQUIPMENT-----

SALE • RENTAL • SERVICE

353 SOUTH CENTRAL AVENUE • LOS ANGELES, CA 90013-1784

(213) 625-0185 • (800) 992-0100 • 24 HR. FAX (213) 625-0826

www.stemarinc.com