



VIBPLATE SPECIFICATIONS

With all the features you need:

- 1 **Reliable engine** – Honda GX-160 offers easy starting and low oil shutdown for durability.
- 2 **Cyclonic pre-cleaner** – captures most airborne contaminants for engine protection and extended service life.
- 3 **Single cast baseplate and eccentric housing** – lower center of gravity and increases travel speed by 12% for greater productivity.
- 4 **Hour / Tachometer** – Measures run time and engine RPM.
- 5 **Protective frame** – Tubular steel roll bar protects engine components and provides central lifting point.
- 6 **Anti-vibration handle** – Dramatically reduces operator fatigue and increases productivity. Up to 50% less vibration than competitive designs.
- 7 **Sealed belt cover** – Keeps dirt and rocks out of and extends belt life.
- 8 **Convenient oil drain** – Facilitates easy access to engine oil for maintenance.
- 9 **Cog-tooth belt drive** – Enables longer life compared to conventional V-belts.
- 10 **Removable water tank** – Easy refilling and removable without tools (largest in it's class).
- 11 **Open base plate design** – Makes for easier removal of dirt and rock build-up. Cast Iron construction for durability.



MQ-MVC88VTHW	
STEMAR Rental Class No.	7521
STEMAR Sales Item No.	VIBPLATE 200

MVC88VTHW

Weight lb (kg) - 229 (104)

Plate size WxL in (mm) - 19.7x20.7 (500x525)

Plate - Cast iron

Tank size qt. (ltr) - 13.7 (13.0)

Cyclonic Pre-Cleaner - Dual

Model	Plate Size WxL in. (mm)	Centrifugal Force lbs. (kN)	Exciter Speed VPM	Speed ft./min. (m/min)	Gasoline Engine	Start Method	HP Rating BHP (kw)*	Tank Capacity qt. (ltr)	Operating Weight lbs. (kg)
MVC88VTHW	19.7x20.7 (500x525)	3,372 (15)	6,000	82 (25)	Honda GX-160	Recoil	4.8 (3.6)	13.7 (13.0)	229 (104)